

Model No	Replace Yuasa&Other Suppliers#	Voltage(V)	Capacity(Ah)	L	W	H	
DTZ7S-BS	YTZ7S	12		5.5	114	70	106
DTZ5S-BS	YTZ5S-BS	12		4	114	70	85
DTZ14-BS-C	YTZ14S	12		11.2	150	87	110
DTZ12-BS-C	YTZ12S	12		11.2	150	87	110
DTZ10-BS-C	YTZ10S	12		8.6	150	87	95
DTX9L-BS	YTX9L-BS	12		8	150	87	105
DTX9-BS(W)	YTX9-BS	12		8	150	87	105
DTX9-BS	YTX9-BS	12		8	150	87	105
DTX7L-BS	YTX7L-BS	12		6	114	70	130
DTX7-BS	YTX7-BS	12		6	114	70	130
DTX7A-BS(W)	YTX7A-BS	12		6	150	87	93
DTX7A-BS	YTX7A-BS	12		6	150	87	93
DTX6.5L-BS	YTX6.5L-BS	12		6.5	139	66	102
DTX6.5-BS	YTX6.5-BS	12		6.5	139	66	102
DTX5L-BS	YTX5L-BS	12		4	114	70	106
DTX4L-BS	YTX4L-BS	12		3	114	70	85
DTX4B-BS	YT4B-BS	12		2.3	113	39	85
DTX4A-BS	YTR4A-BS	12		2.3	113	48	85
DTX30L-BS	YIX30L	12		30	168	127	177
DTX30-BS	YIT30	12		30	168	127	177
DTX24HL-BS	YTX24HL-BS	12		24	205	87	162
DTX20L-BS(V)	YTX20L-BS	12		18	175	87	155
DTX20L-BS	YTX20L-BS	12		18	175	87	155
DTX20HL-BS	YTX20HL-BS	12		18	175	87	155
DTX20H-BS	YTX20H-BS	12		18	175	87	155
DTX20CH-BS	YTX20CH-BS	12		18	150	87	161
DTX20-BS(W)	YTX20-BS	12		18	175	87	155
DTX20-BS	YTX20-BS	12		18	175	87	155
DTX19L-BS	YB16L-B	12		19	175	100	155
DTX19CL-BS	YB16CL-B	12		21	175	100	175
DTX19-BS	YB16-B	12		19	175	100	155
DTX18L-BS	YTX18L-BS	12		20	205	87	162
DTX18-BS	YTX18-BS	12		20	205	87	162
DTX16L-BS-1	YTX16L-BS-1	12		14	150	87	159
DTX16L-BS	YTX16L-BS	12		14	150	87	159
DTX16-BS-1	YTX16-BS-1	12		14	150	87	159
DTX16-BS	YTX16-BS	12		14	150	87	159
DTX15L-BS	YTX15L-BS	12		13	175	87	130
DTX15-BS	YTX15-BS	12		13	175	87	130
DTX14L-BS	YTX14L-BS	12		12	150	87	146
DTX14H-BS	YTX14H-BS	12		12	150	87	146
DTX14-BS	YTX14-BS	12		12	150	87	146
DTX14AHL-B	YTX14AHL-BS	12		13	134	89	166
DTX14AH-BS	YTX14AH-BS	12		13	134	89	166
DTX12L-BS	YTX12L-BS	12		10	150	87	130
DTX12-BS(W)	YTX12-BS	12		10	150	87	130
DTX12-BS	YTX12-BS	12		10	150	87	130
DTX12A-BS-C	YT12A-BS	12		10	150	87	106
DTR9-BS-C	YTR9-BS	12		8	150	87	106

DT9B-BS-C	YT9B-BS	12	7.5	150	69	105	
DT7B-BS-C	YT7B-BS	12	5.5	150	65	93	
DT14B-BS-C	YT14B-BS	12	11.5	150	69	145	
DT12B-BS-C	YT12B-BS	12	10	150	69	130	
DB9L-BS	YB9L-B	12	9	135	76	137	
DB9-BS	YB9-B	12	9	135	76	137	
DB7L-BS		12	7	135	75	130	
DB7H-BS	YB7-A,YB7-B	12	8	135	75	130	
DB7-BS		12	7	135	75	130	
DB7BL-BS		12	7	147	59	130	
DB7B-BS	YB7B-B	12	7	147	59	130	
DB6L-BS		12	6	141	73	94	
DB6-BS		12	6	141	73	94	
DB5L-BS	YB5L-B	12	5	120	61	128	
DB4L-BS	YB4L-B	12	4	120	70	92	
DB3L-BS	YB3L-B	12	3	99	57	108	
DB30CL-BS	YB30CL-B	12	30	168	132	192	
DB2.5L-BS	YB2.5L-C	12	2.5	80	71	103	
DB12C-BS-2	YB12C-A	12	12	134	80	160	
DB12AL-BS-2		12	12	134	80	160	
DB12AL-BS	YB12AL-A	12	12	134	80	160	
DB12A-BS-2		12	12	134	80	160	
DB12A-BS	YB12A-A,YB12A-B	12	12	134	80	160	
DB10L-BS-2	YB10L-A2,YB10L-B2	12	11	134	89	145	
DB10L-BS	YB10L-B	12	11	134	89	145	
DB10-BS-2		12	11	134	89	145	
DB10-BS		12	11	134	89	145	
DB10AL-BS-2		12	11	134	89	145	
DB10AL-BS		12	11	134	89	145	
DB10A-BS-2	YB10A-A2	12	11	134	89	145	
DB10A-BS	YB10A-A2	12	11	134	89	145	
D60-N30L-B		53030	12	30	186	130	170
D50-N18L-B	Y50-N18L-A		12	20	205	87	162

HL	Weight(kg)	Charge Current(A)	Assembly Figure	Terminal Type	CA
106	1.55	0.55		4	60
85	1.19	0.40		4	45
110	2.93	1.12		9	140
110	2.93	1.12		9	140
95	2.31	0.86		9	130
105	2.44	0.80		4	90
105	2.17	0.80		4	0
105	2.44	0.80		4	90
130	1.89	0.60		4	75
130	1.89	0.60		4	75
93	1.75	0.60		4	0
93	1.97	0.60		4	85
102	1.79	0.65		5	60
102	1.79	0.65		5	60
106	1.46	0.40		4	55
85	1.11	0.30		4	40
85	0.78	0.23		11	30
85	0.83	0.23		10	30
177	7.18	3.00		4	280
177	7.18	3.00		4	280
162	5.72	2.40		4	300
155	4.49	1.80		4	0
155	4.81	1.80		4	210
155	4.60	1.80		4	250
155	4.60	1.80		4	250
161	4.43	1.80		9	220
155	4.49	1.80		4	0
155	4.81	1.80		4	210
155	4.99	1.90		4	190
175	5.91	2.10		4	210
155	4.99	1.90		4	190
162	5.89	2.00		4	240
162	5.89	2.00		4	240
159	3.95	1.40		1	200
159	3.95	1.40		4	200
159	3.95	1.40		1	200
159	3.95	1.40		4	200
130	3.78	1.30		4	180
130	3.78	1.30		4	180
146	3.47	1.20		4	180
146	3.57	1.20		4	200
146	3.47	1.20		4	180
166	3.59	1.30		4	160
166	3.59	1.30		4	160
130	2.97	1.00		4	160
130	2.84	1.00		4	0
130	2.97	1.00		4	160
106	2.53	1.00		9	120
106	2.33	0.80		9	120

105	2.08	0.75	9	80
93	1.69	0.55	9	70
145	3.00	1.15	9	135
130	2.63	1.00	9	110
137	2.25	0.90	5	90
137	2.25	0.90	5	90
130	1.90	0.70	5	70
130	2.09	0.80	5	80
130	1.90	0.70	5	70
130	1.84	0.70	5	70
130	1.84	0.70	5	70
94	1.61	0.60	5	75
94	1.61	0.60	5	75
128	1.50	0.50	4	60
92	1.42	0.40	4	50
108	0.96	0.30	5	32
192	7.03	3.00	4	300
103	0.79	0.25 —		25
175	3.38	1.20	4	160
160	3.38	1.20	4	160
160	3.38	1.20	5	160
160	3.38	1.20	4	160
160	3.38	1.20	5	160
145	3.07	1.10	4	140
145	3.07	1.10	5	140
145	3.07	1.10	4	140
145	3.07	1.10	5	140
158	3.07	1.10	4	140
158	3.07	1.10	5	140
158	3.07	1.10	4	140
158	3.07	1.10	5	140
170	7.25	3.00	3	300
162	5.89	2.00	4	240

CCA/-18°C