

Model No	Replace Yuasa&Other Suppliers#	Voltage(V)	Capacity(Ah)	L	W	H
B49-6		6		10	91	83 160
B39-6		6		7	126	48 126
B38-6A		6		13	119	83 161
6N6-3B I		6		5	99	57 110
6N6-3B-1 I		6		5	99	57 110
6N6-3B-1		6		6	99	57 110
6N6-3B		6		6	99	57 110
6N6-1D-2		6		6	99	57 110
6N6-1D		6		6	99	57 110
6N6-1C		6		6	99	57 110
6N6-1B-1		6		6	99	57 110
6N6-1B		6		6	99	57 110
6N5.5-1D-1		6		5.5	88	68 97
6N5.5-1D		6		5.5	88	68 97
6N4C-1B		6		4	70	70 103
6N4B-2A-5		6		4	100	47 96
6N4B-2A-4		6		4	100	47 96
6N4B-2A-3		6		4	100	47 96
6N4B-2A		6		4	100	47 96
6N4A-4D-1		6		4	60	56 125
6N4A-4D		6		4	60	56 125
6N4-2A-7		6		4	70	70 95
6N4-2A-6		6		4	70	70 95
6N4-2A-4		6		4	70	70 95
6N4-2A-3		6		4	70	70 95
6N4-2A-2		6		4	70	70 95
6N4-2A		6		4	70	70 95
6N4.5-1D		6		4.5	124	50 87
6N2A-2C-3		6		2	70	46 103
6N2A-2C		6		2	70	46 103
6N2-2A-8		6		2	70	46 95
6N2-2A-4		6		2	70	46 95
6N2-2A-3		6		2	70	46 95
6N2-2A-2		6		2	70	46 95
6N2-2A-1		6		2	70	46 95
6N2-2A		6		2	70	46 95
6N18-3B(W)		6		13	122	86 140
6N18-3B		6		13	122	86 140
6N18-1B		6		14	106	82 143
6N12A-2D		6		12	155	56 114
6N12A-2C		6		12	155	56 114
6N11A-4A		6		11	121	59 129
6N11A-4		6		11	121	58 130
6N11A-3B		6		11	121	59 129
6N11A-3A		6		11	121	59 129
6N11A-3		6		11	121	58 130
6N11A-1B		6		10	122	62 132
6N11-2D		6		11	151	71 100
3-MA-8		6		8	84	94 143

12N9Y-3B	12	9	136	76	138
12N9-4B-1	12	9	135	75	138
12N9-3B	12	9	135	75	138
12N9-3A-1	12	9	135	75	138
12N9-3A	12	9	137	75	139
12N7D-3B	12	7	134	76	141
12N7C-3D	12	8	130	90	116
12N7A-4A	12	7	146	60	132
12N7A-3A	12	7	146	60	132
12N7-4B	12	8	137	75	134
12N7-4A	12	8	137	75	134
12N7-3B	12	8	137	75	134
12N7-3A	12	8	137	75	134
12N6-4B	12	6	141	73	94
12N6-4A	12	6	136	71	94
12N6-3B	12	6	141	73	94
12N6-3A	12	6	136	71	94
12N6.5-4B	12	6.5	140	72	106
12N6.5-3B	12	6.5	140	72	106
12N5-4B	12	5	120	60	130
12N5-3B	12	5	120	60	130
12N5.5A-3B	12	5.5	104	91	115
12N5.5-4B	12	5.5	138	61	131
12N5.5-4A	12	5.5	139	62	128
12N5.5-3B	12	5.5	138	61	131
12N5.5-3A	12	5.5	139	62	128
12N4-3B I	12	3	120	70	92
12N24-4A I	12	20	184	124	158
12N24-4A	12	24	184	124	158
12N24-4 I	12	20	184	124	158
12N24-4	12	24	184	124	158
12N24-3A I	12	20	184	124	158
12N24-3A	12	24	184	124	158
12N24-3 I	12	20	184	124	158
12N24-3	12	24	184	124	158
12N18-4A	12	18	206	92	160
12N18-3A	12	18	206	92	160
12N18-3	12	18	206	92	160
12N14-4A I	12	11	134	89	164
12N14-3B I	12	11	134	89	164
12N14-3A I	12	11	134	89	164
12N12-3B	12	12	200	75	135
12N12-3A	12	12	200	75	135
12N11-3B	12	11	134	90	155
12N11-3A-1	12	11	134	90	155
12N11-3A	12	11	134	90	155
12N10-3B I	12	8.5	134	90	145
12N10-3A-2 I	12	8.5	134	90	145
12N10-3A I	12	8.5	134	90	145
51913	12	19	185	82	170

51814

12

19 185 82 170

HL	Weight(kg)	Charge Current(A)	Assembly Figure	Terminal Type	CA
160	1.18	1.00		5	80
126	0.93	0.70		5	60
161	1.52	1.30		5	104
110	0.70	0.50		5	48
110	0.70	0.50		5	48
110	0.79	0.60		5	48
110	0.79	0.60		5	48
110	0.78	0.60			48
110	0.78	0.60			48
110	0.78	0.60			48
110	0.78	0.60			48
110	0.78	0.60			48
97	0.80	0.55			40
97	0.80	0.55			40
103	0.61	0.40			24
96	0.51	0.40			24
96	0.51	0.40			24
96	0.51	0.40			24
96	0.51	0.40			24
125	0.63	0.40			35
125	0.63	0.40			35
95	0.59	0.40			25
95	0.59	0.40			25
95	0.59	0.40			25
95	0.59	0.40			25
95	0.59	0.40			25
95	0.59	0.40			25
105	0.78	0.45		5	36
103	0.42	0.20			20
103	0.42	0.20			20
95	0.42	0.20			20
95	0.42	0.20			20
95	0.42	0.20			20
95	0.42	0.20			20
95	0.42	0.20			20
140	1.49	1.30		12	
140	1.70	1.30		12	104
143	1.73	1.40		5	90
114	1.38	1.20		5	120
114	1.38	1.20		5	120
129	1.34	1.10		5	88
130	1.34	1.10		5	88
129	1.34	1.10		5	88
129	1.34	1.10		5	88
130	1.34	1.10		5	88
132	1.20	1.00		5	88
100	1.46	1.10		5	88
165	1.63	0.80		12	40

138	2.26	0.90	13	90
138	2.11	0.90	5	90
138	2.11	0.90	5	90
138	2.11	0.90	5	90
139	2.12	0.90	8	90
141	1.82	0.70	5	75
116	2.35	0.80	1	80
132	1.90	0.70	5	74
132	1.90	0.70	5	74
134	2.04	0.80	5	90
134	2.04	0.80	5	90
134	2.04	0.80	5	90
134	2.04	0.80	5	90
94	1.45	0.60	5	60
94	1.45	0.60	5	60
94	1.45	0.60	5	60
94	1.45	0.60	5	60
106	1.77	0.65	5	65
106	1.77	0.65	5	65
130	1.45	0.50	5	40
130	1.45	0.50	5	40
115	1.71	0.55	5	44
131	1.55	0.55	5	60
128	1.55	0.55	5	60
131	1.55	0.55	5	60
128	1.55	0.55	5	60
92	0.96	0.30	4	
174	4.78	2.00	3	225
174	5.14	2.40	3	225
174	4.78	2.00	3	225
174	5.14	2.40	3	225
174	4.78	2.00	3	225
174	5.14	2.40	3	225
174	4.78	2.00	3	225
174	5.14	2.40	3	225
160	4.00	1.80	4	164
160	4.00	1.80	4	164
160	4.02	1.80	5	164
164	2.67	1.10	4	128
164	2.67	1.10	4	128
164	2.67	1.10	4	128
135	2.77	1.20	5	113
135	2.77	1.20	5	113
155	2.60	1.10	5	103
155	2.60	1.10	4	103
155	2.60	1.10	5	103
145	2.23	0.85	5	95
145	2.23	0.85	4	95
145	2.23	0.85	5	95
170	4.81	1.90	3	150

170

4.81

1.90

3

150

CCA/-18°C